



Alumiguard Series Steel Echno-Grille Model 150



Operation

- manual lift
- Internal or central motors

Furnish

Rolling Steel Gates Series 100 or 150 as manufactured by ADT complete with curtain, hood, guides, counterbalance and options as specified.

Highlights

- Economically Priced
- Heavy Duty Construction
- XT2000 motor drive system

Curtain

Construction shall be brick pattern or straight pattern. Continuous horizontal solid rods 2.25" o.c. are to be covered with tubular spacers. Spacer to be vinyl. Links to be aluminum. Rods to be 5/16" bright basic or galvanized wire. Bottom of grille shall be fitted with a bottom bar. Available spacers colors are: Bronze, Silver, Black, and Gold.

Bottom Bar

Shall consist of an interlocking slat carriage bolted to a 2" x 2" x 1/8" hot rolled angle. Lifting handle is centered.

Locking

"Hasps and Pins" consists of galvanized steel pin padlocked to a steel hasp welded to the track.

Spring Counterbalance

Computer designed. Using ADT Helical Power Pack springs. Housings rotate around a fixed pipe shaft using steel cup bearings.

End Bracket

Shall be of sufficient gauge to minimize deflection. Each plate has welded angle pipe support to accept spring shaft assembly.

Guides

To be rolled formed from 11 gauge steel into a 2.5" deep channel with 3/8" returns. Guide is a field welded to mounting angle, minimum 2" x 2" x 1/8" hot rolled.

Hoods

Shall consist of #24 U.S. gauge steel. Hoods are designed to protect and house counterbalance assembly.

Finish

All exposed non-galvanized surfaces shall receive a shop coat of rust inhibiting primer.

Installation

To be by ADT or by an authorized dealer.

Advanced Door Technologies (570) 421-5929
34 North Crystal Street, East Stroudsburg, PA 18301
570-421-59290 877-238-1001 Fax 570-421-1795
www.adtdoor.com